

# Technical information

## Atmoz 2-75



### Characteristics

- With two sealing bars as standard (front/rear)
- Optional at no extra cost: Two sealing bars (left/right)
- Double seal as standard (two sealing wires)  
Optional at no extra cost: Cut-off seal/Wide seal (10 mm)
- Easy-to-remove silicone holders for easy cleaning
- Digital time control with ten-program memory as standard
- Flat working plate
- Supplied with one layer of insert plates for a faster cycle and good product positioning
- Stainless steel casing

### Options

- 1-2 Cut-off seal
- Sensor control
- Liquid control
- Advanced Control System (ACS)
- Gas flush (incl. compressed air connection)
- Soft Air to protect the product and vacuum bag

### Accessories

- Thermal label printer (only in combination with ACS)
- Inclined insert plate (for liquids and powders)
- Second layer of insert plates
- Maintenance set for standard maintenance



Specs	Atmoz 2-75	
Chamber LxWxH (mm)	760x660x280	
Machine LxWxH (mm)	1210x1545x1105	
Voltage	400V-3-50Hz 230V-3-50Hz 220V-3-60Hz 200V-3-50/60Hz	
Pump capacity 50 Hz/60 Hz (m3)	160 / 192	
Machine cycle 50 Hz/60 Hz (sec.)	15 - 40 / 13 - 35	
Power (kW)	4,0 - 4,8	
Weight (kg)	462	
Net seal length (mm)		
- standard	2 x 660	
- option	2 x 880	
Sealing bar configuration	standard	option
- standard		
- option		

### Dimensions mm

