

## Technical information

# Boxer 30



### Characteristics

- Supplied with one sealing bar as standard (front)
- Double seal as standard (two sealing wires).  
Optional at no extra cost: Cut-off/Wide seal
- Easy-to-remove sealing bar for easy cleaning
- Pump maintenance and cleaning program
- Digital time control with ten-program memory as standard
- Soft Air as standard to protect the product and vacuum bag
- Stainless steel casing and transparent lid
- Supplied with two insert plates for a faster cycle and good product positioning

### Options

- Sensor control
- Advanced Control System (ACS)
- Liquid control
- Gas flush

### Accessories

- Thermal label printer (only in combination with ACS)
- Inclined insert plate (for liquids and powders)
- External adapter
- Maintenance set for standard maintenance
- Trolley with shelves



Specs	Boxer 30
Chamber LxWxH (mm)	370x350x150
Machine LxWxH (mm)	555x450x365
Voltage	230V-1-50Hz 100V-1-50/60Hz 110/115V-1-60Hz 220V-1-60Hz
Pump capacity 50 Hz/60 Hz (m3)	8 / 10
Machine cycle 50 Hz/60 Hz (sec.)	19-50 / 17-44
Power (kW)	0,4 - 0,5
Weight (kg)	46
Net seal length (mm)	345
Standard sealing bar configuration	

### Dimensions mm

